

Slim Metal Series Analog Clocks

POE / IP Clocks



Get your facility synchronized and stay that way! OneVue Clocks make it easy by leveraging the power of your existing wireless or Ethernet network. Simply preconfigure the clocks online through our intuitive OneVue interface. When the clocks are delivered, plug them in to PoE Power (Power over Ethernet) and hang them on the wall. The clocks will immediately access your network to keep your organization running on time, even through power outages and Daylight Saving Time shifts.

Slim Metal Series Analog Clocks

Contemporary frames offer an upscale, executive look to our high-performance clocks. These high-tech synchronized clocks are easy to install and are easily incorporated into any décor.

POE SLIM METAL SERIES

PART NO.	DESCRIPTION
162-PE110M01	12.5" (31.75cm) Slim Metal, PoE, Configured
162-PE110M02	12.5" (31.75cm) Slim Metal, Healthcare Dial, PoE, Configured
162-PE110M05	12.5" (31.75cm) Slim Metal, General 12/24 Dial, PoE, Configured
162-PE150M01	16" (40.64cm) Slim Metal, PoE, Configured
162-PE150M02	16" (40.64cm) Slim Metal, Healthcare Dial, PoE, Configured
162-PE150M05	16" (40.64cm) Slim Metal, General 12/24 Dial, PoE, Configured



Slim Metal



Slim Metal
General 12/24



Slim Metal
Healthcare

Dual Clock Kit

Create an easy-to-read dual-sided clock for hallways or other large areas with our Dual Clock Kit. The kit includes a bracket, mounting plate and hardware to easily assemble and install two 12.5" (31.75cm) or 16" (40.64cm) Slim Metal Clocks back-to-back.

DUAL CLOCK KIT

PART NO.	DESCRIPTION
199-000042	12.5" (31.75cm) Dual Mounting Kit - Slim Metal
199-000043	16" (40.64cm) Dual Mounting Kit - Slim Metal



Easy-to-assemble bracket kit lets you create a dual-sided clock for hallways or other large areas.



FEATURES

- Automatically adjusts for Daylight Saving Time
- Clock Lock feature can be used to securely mount to the wall
- Clock configuration to access your network is accomplished online prior to delivery for plug-and-play convenience

SLIM METAL SERIES SPECIFICATIONS

- Clock power: PoE 802.3 at/af compatible
- Operating range: 32° - 158°F (0° - 70°C)
- **12.5" Slim Metal**
 - 12.5" (31.75cm) diameter
 - Passivated aluminum bezel with thermoplastic lens
 - 2.5" (6.4cm) deep
- **12.5" Dual-Sided Clock Kit (assembled dimensions)**
 - 12.5" (31.75cm) diameter
 - 5.5" (14.0cm) width
 - 14" (35.6cm) projection from mounting surface (wall or ceiling)
- **16" Slim Metal**
 - 16" (40.64cm) diameter
 - Passivated aluminum bezel with thermoplastic lens
 - Single clock depth: 2.8" (7.1cm)
- **16" Dual-Sided Clock Kit (assembled dimensions)**
 - 16" (40.64 cm) diameter
 - 6.4" (16.2 cm) width
 - 18.2" (46.2 cm) projection from mounting surface (wall or ceiling)

LENS

- Durable thermoplastic lenses

DIALS

- Customized clock faces are available to display your organization's name or logo
- Please call for more information

To Learn More:

Call - 855-602-2934

Email - info@primexinc.com
primexinc.com



©2022 by Primex, Inc.

The Primex logo is a registered trademark of Primex, Inc. All Rights Reserved. 4.6.22